



Emmegi Heat Exchangers Product Lines



AC Fan Driven



2000K & KBV AC Motors

Heat Removals to 16 HP. Optional Internal Bypass Valve. Totally Enclosed Motors. Oil Flows to 50 GPM.



HPV Series I AC Motors

Heat Removals to 70 HP. Internal Bypass Valve Standard. Totally Enclosed Motors. Oil Flows to 100 GPM.



HPV Series II AC Motors

Heat Removals to 265 HP. Internal Bypass Valve Standard. Totally Enclosed Motors. Oil Flows to 350 GPM.

DC Fan Driven



2000K & KBV DC Motors

Heat Removals to 35 HP.
Optional Internal Bypass Valve.
Oil Flows to 125 GPM.



HPV Series DC Motors

Heat Removals to 36 HP. Internal Bypass Valve Standard. Oil Flows to 80 GPM.



S & SBV Series DC Motors

Heat Removals to 38 HP.
Optional Internal Bypass Valve.
Oil Flows to 100 GPM.

Hydraulic Fan Driven



2000K & KBV Hvdraulic Motors

Heat Removals to 30 HP.
Optional Internal Bypass Valve.
Wide range of Hydraulic Motor
Displacements available.
Oil Flows to 50 GPM



HPV Series I Hydraulic Motors

Heat Removals to 130 HP. Internal Bypass Valve Standard. Oil Flows to 100 GPM.



HPV Series II Hydraulic Motors

Heat Removals to 300 HP. Optional Internal Bypass Valve. Oil Flows to 350 GPM.

Cooling Systems



Silent Evo II

Off-line cooling systems with oil cooler & recirculation.
Pump heat removals to 60 HP.



RID Series

Gearbox cooling systems with oil cooler, recirculation pump & filter heat removals to 25 HP.



HPATK

Combination reservoir, oil cooler, & suction filter. Ideal for closed loop hydrostatic cooling.

Water / Oil



WB Series Water/Oil

Stainless steel Water/Oil Coolers. Compact water saving design. Heat Removals to 360 HP. Oil Flows to 200 GMP.



MG Series Water/Oil

Sea Water duty shell & tube heat exchangers.

Corrosion resistant copper-nickel cooling tubes & bronze end bonnets.



Water Modulating Valves

Control water flow through Water/Oil heat exchangers to maintain desired oil temperatures.

No external input required.

Accessories



AC Temperature Switches

Cycle cooling fan to maintain desired temperatures.

Fixed & adjustable designs available.



DC Temperature Switches

12v & 24v Models. TMR Switches are prewired & include relay for plug & play operation.



Thermostatic Valves

Modulating valves bypass oul during cold startup.

#8 through #24 sizes available.





